




CONTROL H SC



General Construction

- Conductor:** Flexible bare copper strand (Class 5)
CPR-classification acc. to EN 50575: Dca
- Insulation:** FRNC-compound HI2
- Color Cores:** X: numbers
G: green/yellow + numbers
- Shield:** Tinned copper braid; coverage 70%
- Sheath:** Outer sheath: FRNC-compound HM2
Color: Grey RAL 7001

Technical data

- Nominal Voltage:** 300/500 V
- Test voltage:** 2 kV
- Temperature:** -30 °C to +70 °C (fixed) -5 °C to +70 °C (flex)
- Flame Resistance:** VDE 0482-266-2-4 / IEC 60332-3-24 (Cat. C)
- Oil Resistance:** Yes

Movement Data @20°C

- Bending radius:** 5 x D (fixed) / 10 x D (flex)

Approval

- Halogen free according to CEI EN 60754-1 / VDE 0482-754-1 - UV Resistance

Name	Cable type	Ø mm	Weight Kg/Km
FIXHSC2X0,50	2 x 0,5	5,8	47,0
FIXHSC3G0,50	3 x 0,5	6,2	55,0
FIXHSC4G0,50	4 x 0,5	6,6	66,0
FIXHSC5G0,50	5 x 0,5	7,2	80,0
FIXHSC7G0,50	7 x 0,5	8,6	108,0
FIXHSC10G0,50	10 x 0,5	9,3	135,0
FIXHSC12G0,50	12 x 0,5	9,9	162,0
FIXHSC18G0,50	18 x 0,5	11,9	227,0
FIXHSC25G0,50	25 x 0,5	13,7	317,0
FIXHSC2X0,75	2 x 0,75	6,4	58,0
FIXHSC3G0,75	3 x 0,75	6,7	70,0
FIXHSC4G0,75	4 x 0,75	7,5	80,0
FIXHSC5G0,75	5 x 0,75	8,1	100,0
FIXHSC7G0,75	7 x 0,75	9,0	133,0
FIXHSC10G0,75	10 x 0,75	10,3	164,0
FIXHSC12G0,75	12 x 0,75	11,3	203,0
FIXHSC18G0,75	18 x 0,75	13,5	284,0
FIXHSC25G0,75	25 x 0,75	15,8	380,0
FIXHSC2X1	2 x 1	6,6	64,0
FIXHSC3G1	3 x 1	6,9	80,0
FIXHSC4G1	4 x 1	7,5	98,0
FIXHSC5G1	5 x 1	8,5	121,0
FIXHSC7G1	7 x 1	9,5	160,0
FIXHSC10G1	10 x 1	10,9	202,0
FIXHSC12G1	12 x 1	11,7	245,0
FIXHSC18G1	18 x 1	13,9	376,0
FIXHSC25G1	25 x 1	16,4	502,0

*All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.



Name	Cable type	Ø mm	Weight Kg/Km
FIXHSC2X1,5	2 x 1,5	7,5	97,0
FIXHSC3G1,5	3 x 1,5	7,9	119,0
FIXHSC4G1,5	4 x 1,5	8,2	125,0
FIXHSC5X1,5	5 x 1,5	8,9	182,0
FIXHSC5G1,5	5 x 1,5	8,9	182,0
FIXHSC7X1,5	7 x 1,5	10,5	232,0
FIXHSC7G1,5	7 x 1,5	10,5	232,0
FIXHSC10G1,5	10 x 1,5	12,1	298,0
FIXHSC12X1,5	12 x 1,5	13,2	360,0
FIXHSC12G1,5	12 x 1,5	13,2	360,0
FIXHSC18G1,5	18 x 1,5	15,6	507,0
FIXHSC25X1,5	25 x 1,5	18,2	694,0
FIXHSC25G1,5	25 x 1,5	18,2	694,0
FIXHSC2X2,5	2 x 2,5	8,5	132,0
FIXHSC3G2,5	3 x 2,5	9,3	160,0
FIXHSC4G2,5	4 x 2,5	10,0	194,0
FIXHSC5G2,5	5 x 2,5	11,5	386,0
FIXHSC7G2,5	7 x 2,5	13,8	498,0
FIXHSC10G2,5	10 x 2,5	15,0	604,0
FIXHSC12X2,5	12 x 2,5	17,0	710,0
FIXHSC12G2,5	12 x 2,5	17,0	710,0
FIXHSC18G2,5	18 x 2,5	19,3	796,0
FIXHSC25X2,5	25 x 2,5	28,7	980,0
FIXHSC2X4	2 x 4	10,0	209,0
FIXHSC3G4	3 x 4	10,7	249,0
FIXHSC4G4	4 x 4	11,9	288,0
FIXHSC5G4	5 x 4	13,1	337,0

*All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.



Name	Cable type	Ø mm	Weight Kg/Km
FIXHSC7G4	7 x 4	15,1	488,0
FIXHSC2X6	2 x 6	11,9	278,0
FIXHSC3G6	3 x 6	12,5	347,0
FIXHSC4G6	4 x 6	14,2	399,0
FIXHSC5G6	5 x 6	16,0	670,0
FIXHSC7G6	7 x 6	19,2	770,0
FIXHSC2X10	2 x 10	14,9	434,0
FIXHSC3G10	3 x 10	15,9	501,0
FIXHSC4G10	4 x 10	17,8	698,0
FIXHSC5G10	5 x 10	19,6	828,0
FIXHSC7G10	7 x 10	21,6	1.254,0
FIXHSC4G16	4 x 16	20,8	987,0
FIXHSC5G16	5 x 16	22,9	1.207,0
FIXHSC7G16	7 x 16	25,2	1.816,0
FIXHSC3G25	3 x 25	24,8	1.214,0
FIXHSC4G25	4 x 25	26,2	1.592,0
FIXHSC5G25	5 x 25	29,4	2.002,0
FIXHSC3G35	3 x 35	27,9	1.622,0
FIXHSC4G35	4 x 35	33,5	2.380,0
FIXHSC5G35	5 x 35	33,8	2.664,0
FIXHSC3G50	3 x 50	35,7	2.471,0
FIXHSC4G50	4 x 50	39,2	3.003,0
FIXHSC5G50	5 x 50	43,3	3.882,0
FIXHSC3G70	3 x 70	41,4	3.840,0
FIXHSC4G70	4 x 70	45,3	4.939,0
FIXHSC5G70	5 x 70	49,6	6.572,0
FIXHSC3G95	3 x 95	47,7	5.651,0

*All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.



Name	Cable type	Ø mm	Weight Kg/Km
FIXHSC4G95	4 x 95	52,4	6.690,0
FIXHSC5G95	5 x 95	57,5	8.370,0
FIXHSC3G120	3 x 120	51,0	6.342,0
FIXHSC4G120	4 x 120	56,1	8.453,0

*All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.

