


CONTROL H









General Construction

Conductor: Flexible bare copper (Class 5)

CPR- classifica6on acc. to EN 50575: Dca

Insulation: FRNC-compound HI2

Color Cores: X: numbers

G: green/yellow + numbers

Outer sheath: FRNC-compound HM2 Sheath:

Color: Grey RAL 7001

Technical data

Nominal Voltage: 300/500 V

Test voltage:

-30 °C to +70 °C (fixed) -5 °C to +70 °C (flex) **Temperature:**

Flame Resistance: VDE 0482-266-2-4 / IEC 60332-3-24 (Cat. C)

Oil Resistance: Yes

Movement Data @20°C

Bending radius: 5 x D (fixed) / 10 x D (flex)

Approval



Halogen free according to CEI EN 60754-1 / VDE 0482-754-1 - UV Resistance








Name	Cable type	Ø mm	Weight Kg/Km
FIXH2X0,50	2 x 0,5	5,1	38,0
FIXH3G0,50	3 x 0,5	5,7	43,0
FIXH4G0,50	4 x 0,5	6,2	54,0
FIXH5G0,50	5 x 0,5	6,6	65,0
FIXH7G0,50	7 x 0,5	7,2	82,0
FIXH10G0,50	10 x 0,5	9,1	119,0
FIXH12G0,50	12 x 0,5	9,1	133,0
FIXH2X0,75	2 x 0,75	5,5	33,0
FIXH3G0,75	3 x 0,75	6,0	66,0
FIXH4G0,75	4 x 0,75	6,5	78,0
FIXH5G0,75	5 x 0,75	7,0	91,0
FIXH7G0,75	7 x 0,75	7,5	124,0
FIXH10G0,75	10 x 0,75	10,1	162,0
FIXH12G0,75	12 x 0,75	10,2	191,0
FIXH18G0,75	18 x 0,75	11,9	283,0
FIXH25G0,75	25 x 0,75	14,9	388,0
FIXH34G0,75	34 x 0,75	16,4	641,0
FIXH37G0,75	37 x 0,75	17,2	715,0
FIXH41G0,75	41 x 0,75	17,6	795,0
FIXH42G0,75	42 x 0,75	17,8	800,0
FIXH50G0,75	50 x 0,75	19,8	815,0
FIXH61G0,75	61 x 0,75	20,9	1.028,0
FIXH2X1	2 x 1	5,7	58,0
FIXH3X1	3 x 1	6,4	68,0
FIXH3G1	3 x 1	6,4	68,0
FIXH4G1	4 x 1	7,0	85,0
FIXH5G1	5 x 1	7,8	110,0

^{*}All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.





Name	Cable type	Ø mm	Weight Kg/Km
FIXH7G1	7 x 1	8,1	148,0
FIXH8G1	8 x 1	9,4	200,0
FIXH10G1	10 x 1	10,4	232,0
FIXH12G1	12 x 1	11,1	245,0
FIXH16G1	16 x 1	12,0	328,0
FIXH18G1	18 x 1	13,4	363,0
FIXH20G1	20 x 1	13,5	438,0
FIXH25G1	25 x 1	16,2	531,0
FIXH34G1	34 x 1	17,4	688,0
FIXH37G1	37 x 1	18,4	833,0
FIXH41G1	41 x 1	18,9	925,0
FIXH42G1	42 x 1	18,9	935,0
FIXH50G1	50 x 1	21,0	978,0
FIXH61G1	61 x 1	22,2	1.140,0
FIXH65G1	65 x 1	22,8	1.304,0
FIXH2X1,5	2 x 1,5	6,3	87,0
FIXH3G1,5	3 x 1,5	7,3	95,0
FIXH4G1,5	4 x 1,5	7,8	117,0
FIXH5G1,5	5 x 1,5	8,9	152,0
FIXH7G1,5	7 x 1,5	9,8	192,0
FIXH8G1,5	8 x 1,5	10,6	278,0
FIXH10G1,5	10 x 1,5	11,7	309,0
FIXH12G1,5	12 x 1,5	13,2	312,0
FIXH16G1,5	16 x 1,5	13,8	415,0
FIXH18G1,5	18 x 1,5	15,2	456,0
FIXH20G1,5	20 x 1,5	15,9	585,0
FIXH25G1,5	25 x 1,5	17,2	638,0

^{*}All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.




MOVINFLEX Leading cable solutions

Name	Cable type	Ø mm	Weight Kg/Km
FIXH34G1,5	34 x 1,5	19,8	890,0
FIXH37G1,5	37 x 1,5	20,2	1.140,0
FIXH50G1,5	50 x 1,5	23,7	1.410,0
FIXH61G1,5	61 x 1,5	25,3	1.630,0
FIXH65G1,5	65 x 1,5	26,0	1.810,0
FIXH2X2,5	2 x 2,5	7,7	124,0
FIXH3G2,5	3 x 2,5	9,0	148,0
FIXH4G2,5	4 x 2,5	10,0	236,0
FIXH5G2,5	5 x 2,5	11,0	263,0
FIXH7G2,5	7 x 2,5	12,7	298,0
FIXH8G2,5	8 x 2,5	13,2	378,0
FIXH10G2,5	10 x 2,5	14,7	444,0
FIXH12G2,5	12 x 2,5	16,5	522,0
FIXH16G2,5	16 x 2,5	17,5	730,0
FIXH18G2,5	18 x 2,5	18,4	749,0
FIXH20G2,5	20 x 2,5	18,7	1.070,0
FIXH25G2,5	25 x 2,5	20,8	1.175,0
FIXH30G2,5	30 x 2,5	23,7	1.280,0
FIXH2X4	2 x 4	9,8	195,0
FIXH3G4	3 x 4	11,8	235,0
FIXH4G4	4 x 4	12,0	305,0
FIXH5G4	5 x 4	13,2	363,0
FIXH7G4	7 x 4	16,0	468,0
FIXH8G4	8 x 4	17,8	603,0
FIXH10G4	10 x 4	19,6	798,0
FIXH12G4	12 x 4	20,2	984,0
FIXH16G4	16 x 4	22,8	1.350,0

^{*}All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.





Name	Cable type	Ø mm	Weight Kg/Km
FIXH2X6	2 x 6	12,0	258,0
FIXH3G6	3 x 6	12,7	390,0
FIXH4G6	4 x 6	14,1	465,0
FIXH5G6	5 x 6	16,5	583,0
FIXH7G6	7 x 6	17,6	782,0
FIXH2X10	2 x 10	15,0	490,0
FIXH3G10	3 x 10	16,2	750,0
FIXH4G10	4 x 10	18,0	846,0
FIXH5G10	5 x 10	19,8	917,0
FIXH7G10	7 x 10	22,5	1.283,0
FIXH2X16	2 x 16	17,3	665,0
FIXH3G16	3 x 16	18,7	998,0
FIXH4G16	4 x 16	20,6	1.089,0
FIXH5G16	5 x 16	23,5	1.285,0
FIXH7G16	7 x 16	26,2	1.835,0
FIXH3G25	3 x 25	24,5	1.238,0
FIXH4G25	4 x 25	26,0	1.582,0
FIXH5G25	5 x 25	30,8	1.920,0
FIXH3G35	3 x 35	29,8	1.664,0
FIXH4G35	4 x 35	33,7	1.980,0
FIXH5G35	5 x 35	37,7	2.765,0
FIXH3G50	3 x 50	33,8	2.678,0
FIXH4G50	4 x 50	38,0	2.824,0
FIXH5G50	5 x 50	42,1	4.133,0
FIXH3G70	3 x 70	40,2	3.339,0
FIXH4G70	4 x 70	44,2	4.295,0
FIXH5G70	5 x 70	48,5	5.715,0

^{*}All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.


Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.





Name	Cable type	Ø mm	Weight Kg/Km
FIXH3G95	3 x 95	46,6	4.914,0
FIXH4G95	4 x 95	51,2	5.817,0
FIXH5G95	5 x 95	56,3	7.278,0
FIXH3G120	3 x 120	49,8	5.515,0
FIXH4G120	4 x 120	54,8	7.350,0

Customer responsibility to verify suitability of the product for the intended purpose remains. Processing and application of the goods are outside of our control possibilities. Right to technical changes is reserved.



^{*}All trademarks used herein are the property of their respective owners. Reference to any non-Movinflex trademarks is not intended to claim any endorsement or association between Movinflex and the respective trademark owners, and should not be construed.